

UD

Professional Undercounter Dishwasher/Glasswasher – 500mm Rack W 570mm x D 600mm x H 840mm

The Washtech Professional Range combines the best of modern technology with an uncompromising use of high quality components and heavy duty stainless steel construction. The result is a machine that you can rely on for great wash results for many years to come.

The Washtech UD incorporates intuitive electronic controls providing soft wash start, eco power saver system, easy to read temperatures for HACCP reporting, chemical pump adjustments and priming, cycle customisation, immediate fault diagnosis and much more. The result is a versatile and high capacity undercounter dishwasher/glasswasher that at 600mm deep fits comfortably under most benches.

Standard Features

- Quikstart 1, 2 and 3 minute cycles
- Washes up to 1,080 plates / 1,500 glasses per hour
- QuikConnect Installation with everything you need including:
 - Water supply hose
 - Dual detergent and rinse aid pumps with injector lines
 - Drain pump outlet hose
 - 15 amp plugset
 - No commissioning required
- Reliable results through robust stainless steel wash and rinse arms with precision stainless jets
- Durable stainless steel construction
- Moffat's Comprehensive 5-2-1 Warranty
- Low hot water consumption of 2.6 litres per cycle
- Soft start ensures great wash results through progressively pressurising the cycle to provide a consistent and even clean every time
- EcoPower reduces temperatures and energy consumption when machine is not being used
- Insulated door to reduce noise and heat emission from the machine
- Reliable double filtration system via scrap trays and separate wash inlet filter

Includes:


- 1x 600 70028 - 500mm dish rack
- 1x 600 70029 - 500mm cup rack
- 1x C660503 - cutlery container



UD

Professional Undercounter Dishwasher/Glasswasher – 500mm Rack

W 570mm x D 600mm x H 840mm



MOFFAT®

moffat.com.au

Australia
Moffat Pty Limited

Victoria/Tasmania
740 Springvale Road
Mulgrave, Victoria 3170
Telephone 03-9518 3888
Facsimile 03-9518 3833
vsales@moffat.com.au
www.moffat.com.au

New South Wales
Telephone 02-8833 4111
nswsales@moffat.com.au

South Australia
Telephone 03-9518 3888
vsales@moffat.com.au

Queensland
Telephone 07-3630 8600
qldsales@moffat.com.au

Western Australia
Telephone 08-9202 6820
bgarcia@moffat.com.au

A Hot Water	
Temperature	65°C
Connection	3/4" male hose supplied
Pressure	200-350kPa
Flow	20 litres per min
Quality	Potable & soft
Backflow Prevention	Dual Check Valve (DCV)
Consumption	2.6 litres per cycle
B Waste	
Connection	Hose supplied for 38mm open standpipe 750 high or connection to sink trap
C Electrical	
Single phase	240V 50Hz 15A plugset supplied
Maximum Power Consumption	
Single phase	3.4kW
Heating	
Wash	2.5kW
Rinse	3.0kW

Dimensions	
Width	570mm
Depth	600mm
Height	840mm
Weight	75kg

Packed Dimensions	
Width	690mm
Depth	670mm
Height	970mm
Weight	78kg
Cubicmetres	0.44m ³

Water Quality Requirements						
Hardness	ppm	pH				
Min	20	7				
Max	100	8				

Ions	Cl ⁻	SO ₄	Fe	Mn	Cu	CL ₂
Max mg/l	100	400	0.1	0.5	0.05	0.1

Refer operator manual for installation instructions



ISO9001
All Washtech products are designed and manufactured by Washtech using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Washtech reserves the right to change specifications and design without notice.



© Copyright Moffat Ltd
Moffat / 11.16

an Ali Group Company



The Spirit of Excellence